Atlas Copco Portable Air compressors

The two & three-tool low weight compressor



XAS 67 XAS 87

With a towing weight of under 750 kg, the multi-tool capacity XAS 67-87 Kd range can be towed behind a small car by any person holding a standard driving license. This lightweight advantage is matched to heavyweight performance.

Power comes from a turbocharged and standard Kubota V1505 diesel engine driving a new generation compressor element. The result? More than enough air to drive three pneumatic tools at once, matched to the best fuel efficiency at both low and peak air demands.

Other Atlas Copco features include:

- Total weight for a full option model below 750 kg
- Choice of Zincor™ steel or award winning HardHat™ polyethylene canopy
- Ease of operation, with outlets and controls all in one place
- Wide temperature ability.
 From 20°C (with the cold start aid) up to 50°C







More than 130 years of experience in a light and powerful package

Technical data

	XAS 67	XAS 87
bar	7	7
m³/min	3.6	5
1/s	60	83
dB(A)	98	98
1	40	40
kg	687	687
kg	740	740
	1/s dB(A) 1 kg	bar 7 m³/min 3.6 1/s 60 dB(A) 98 1 40 kg 687

Kubota engine			
Model		V1505	V1505-T
Full load engine speed	rpm	3000	3000
Unload engine speed	rpm	1850	1850
Engine power at full load	kW	26.5	33

Dimensions LxWxH (in mm)		HardHat	Steel
Вох			
Length	mm	1965	1920
Width	mm	1337	960
Height	mm	1112	1009
Adjustable towbar			
Length (min/max) 1)	mm	3157/3513	3132/3488
Width	mm	1336	1330
Height	mm	1340	1244
Fixed towbar			
Length	mm	3078	3053
Width	mm	1336	1330
Height	mm	1340	1252

¹⁾ with ball coupling (Ø 50mm)

Features & options

- Canopy
- Full Zincor™ steel
- HardHat™
- Undercarriage
 - Fixed towbar without brakes
- Adjustable towbar without brakes
- Towbar support
- Support leg
- Jockey wheel
- Towing eye
 - AC / BNA / DIN / GB / ITA / NATO eye
 - Ball coupling Ø 50 mm
- Road signalization
- Full road signalization with 13 pole connector
- Bumper and reflectors
- 13 pole to 7 pole adapter for road signalization
- Wheel chocks
- Anti theft device
- Intake air filter safety cartridge
- Tool lubricator
- Tool box
- Metal fuel tank filler neck
- Cold start aid (down to -20°C)
- Spillage free frame
- COSMOS™ (Comprehensive Service & Monitoring System)
- Customer colors and/or labels

